



REVISIONS			
LTR	DESCRIPTION	DATE	REVISED BY / APPROVED
A	INITIAL RELEASE	03/28/04	J. DEAN / S. LANDIS

SCALE 4:1

- NOTES:
1. BREAK SHARP EDGES & DEBURR.
  2. MACHINED SURFACE FINISH TO BE 125 RMS OR BETTER.
  3. MACHINED FILLETS TO BE .015 MAX.
  4. ANODIZE PER MIL-A-8625, TYPE II, CLASS 2 - BLACK.
  5. ALL DIMENSIONS APPLICABLE BEFORE ANODIZING.

<input checked="" type="checkbox"/>	1	90145A539	φ.250 X .625 18-8 STAINLESS STEEL DOMEL PIN	McMASTER CARR	1
<input type="checkbox"/>	2				
<input type="checkbox"/>	3				
<input type="checkbox"/>	4				
<input type="checkbox"/>	5				
LIST OF MATERIALS					
THIS DRAWING CREATED IN:					
Steward Observatory, University of Arizona					
933 N. Cherry Avenue, Tucson, AZ 85721 (520)621-7850					
DRAWN BY: D. DEAN		DATE: 12/13/04		PROJECT: MMT	
CHECKED BY: S. LANDIS		DATE: 12/13/04		TITLE: CALIBRATION END FITTING PLATE R	
APPROVED BY: M. NEED		DATE: 12/13/04		PLAT TO BE BORED: D -	
MATERIAL: AL ALLOY 6061-T6		NEXT ASSY USED ON: 14450 MMT-MAESTRO		REVISION: 14456 A	
FINISH: 4		ASSEMBLY APPLICATION:		SHEET 1 OF 3	