



SCALE 4:1

- NOTES:
1. BREAK SHARP EDGES & DEBURR.
 2. MACHINED SURFACE FINISH TO BE 125 RMS OR BETTER.
 3. ANODIZE PER MIL-A-8625, TYPE II, CLASS 2 - BLACK.
 4. ALL DIMENSIONS APPLICABLE BEFORE ANODIZING.

REVISIONS				
LTR	DESCRIPTION	DATE	REVIEWED BY	APPROVED
A	INITIAL RELEASE	03/28/04	J. BROWN	S. LANDIS

DO NOT SCALE DRAWING		THIS DRAWING CREATED IN:		Steward Observatory, University of Arizona	
TOLERANCES UNLESS OTHERWISE SPECIFIED		ASAP		833 N. Cherry Avenue, Tucson, AZ 85721 (520)621-7856	
TOLERANCES IN ACCORDANCE WITH SPC 114, 115-04		MICH		PROJECT: MMT	
TOLERANCES		TIGAR		DRAWN BY: D. DEAN	
UNLESS OTHERWISE SPECIFIED		DATE: 06/27/04		CHECKED BY: G. LANDIS	
LINES: 0.005		DATE: 06/27/04		APPROVED BY: M. NEED	
DIMENSIONS: 0.005		DATE: 06/27/04		DATE: 06/27/04	
HORIZONTAL: 0.005		DATE: 06/27/04		TITLE: FOLD MIRROR MOUNTING BLOCK SHIM	
VERTICAL: 0.005		DATE: 06/27/04		DRAWN BY: D. DEAN	
MATERIAL: AL ALLOY 6061-T6		14285		PROJECT NUMBER: 14247	
NEXT ASSY USED ON:		MMT-MAESTRO		REVISION: A	
FINISH: 3		ASSEMBLY APPLICATION:		SHEET 1 OF 1	