

NOTES:

1. MATERIAL: TYPE 410 STAINLESS STEEL, ANNEALED CONDITION.

2. FINISH: VAPOR DEGREASE FOLLOWED BY PRIME AND FINISH COAT WITH:
PRIMER: DEXTER CORPORATION 10-P4-2 EELEAD FREE EPOXY PRIMER, BMS10-11 TYPE 1, .005 TO .007 THICK
FINISH COAT: DEXTER CORPORATION 463-3-8 FLAT BLACK EPOXY TOP COAT TO .003 THICK.

3. INNER BEND RADIUS = .12/.18

REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED
	1	INITIAL ISSUE	2/28/03	E. HERTZ

REMOVE BURRS AND BREAK SHARP EDGES

TOLERANCES ON FRACTIONS ± DECIMALS ± ANGLES ±

SMITHSONIAN ASTROPHYSICAL OBSERVATORY
CENTRAL ENGINEERING

BRACKET, CABLE CARRIER

SIZE	CODE IDENT NO.	DWG NO.	REV
D	50944	WFS2-3029	1

SCALE 1/1 | IDEAS DWG | SHEET 1 OF 1

E. HERTZ 2/28/03

NEXT ASSY WFS-400