- 1. Stow the telescope. TCS-NG-INDI \rightarrow Goto Functions \rightarrow Stow
- 2. Close the telescope mirror covers (in the correct order north first, then south)
- 3. Stow the dome. Use the hand paddle to center the shutter over the eastern dome rotation wheel above the main entry door to the dome.
- 4. Plug in the twist lock AC power cable to the dome shutter motor on the west wall.
- 5. Close the shutter by pressing and releasing the CLOSE button on the shutter control box. Be ready to hit the STOP button until the shutter is fully closed. When the dome is stowed this box is to the south.
- 6. Unplug the twist lock AC power cable to the dome shutter motor on the west wall.
- 7. Disable telescope in XEphem.
- 8. Close Xephem
- 9. Fill out and send a 21" Trouble Report even if there weren't any problems during the night!
- 10. Close all other open applications, windows, etc.
- 11. Shutdown the NGTCS computer in blue rack west of operators table.
- 12. Switch "telescope power" to the OFF position at the observatory control box located on the south wall of the dome.
- 13. Switch "dome power" to the OFF position at the observatory control box (middle black button) located on the south wall of the dome.
- 14. Switch "dome control" to the local position on the observatory control box.

From: https://lavinia.as.arizona.edu/~tscopewiki/ - MOON

Permanent link: https://lavinia.as.arizona.edu/~tscopewiki/doku.php?id=21 inch:normal shutdown&rev=147432182





Last update: 2016/09/19 14:50